

ISEKI SZ ZERO-TURN

MOWERS

The SZ Zero-Turn Mower continues Iseki's tradition of delivering equipment that is reliable, hard-working and offers the most advanced engineering.

It all begins with you – your efficiency, comfort and ability to add value to the bottom line. With the Iseki SZ you can rest easy knowing that you have a diesel engine packing 33hp with the largest radiator on the market in its class. Your Iseki SZ will provide the stability and power needed to handle the toughest of jobs, day in, day out.

Designed and built for the professional operator, the Iseki SZ provides the smooth ride required for those days when many hours are spent behind the wheel. Sensibly laid out controls located within arm's reach add to the driving experience. And with lower operating costs and superior fuel efficiency, the Iseki SZ becomes the perfect partner for your operations.

THE ISEKI

DIFFERENCE

When you choose Iseki, you're not simply buying a tractor or mower, you're investing in 85 years of industry-leading engineering and manufacturing experience. Experience that continues to produce high quality and top performing products that are built to meet today's ever increasing demands.

While Iseki has made its mark internationally, you can still feel confident knowing that we understand the unique industries of each country. During our 28 years in the Australian market we have built solid and reliable foundations, continuously delivering superb products and services that work even harder for your specific needs.

You get the expertise of your local Iseki dealer who will match the right tractor or mower to your business and even provide flexible finance options to help fund your purchase.

Combine this with peace of mind from first-class parts and service support and you'll see what we mean by the Iseki Difference.

FEATURES



MOWER DECK

- Deep deck design to handle large volumes of grass.
- Three blade side discharge deck with large 1.83 m (72") cutting width.
- Robust one piece pressed steel construction.
- Anti-scalloping rollers and gauge wheels for an even cutting height.



DECK LIFT / JACK

- Convenient crank lift mechanism allows the front of the mower to be easily raised.
- Makes regular maintenance, inspection and replacement of blades easy.
- Quick and simple to activate, with no heavy lifting required.
- 45 degree flip-up.



CUTTING HEIGHT ADJUSTMENT

- Cutting height is quickly and easily adjusted by the turn of a dial.
- Numeric setting is clearly visible for accurate calibration.
- Adjustment range from 25 mm to 115 mm.
- Controls are easily accessed from the operator's seat and can be adjusted while on the move.

ISEKI Zero-Turn Diesel Mower 33hp





FOLDING ROPS FRAME

- Foldable ROPS as standard.
- Allows the mower to pass under low overhead obstacles.
- Quick and easy to activate simply remove 2 pins and fold.



SERVICE AND MAINTENANCE

- Full opening hood and folding seat for easy service and maintenance.
- Allows for quick access to all mechanical and operational parts.
- Filling points and filters are easily accessible.



CONTROL PANEL

- Conveniently grouped controls for ease of use and operation while on the move.
- Independent electro hydraulic PTO engagement.
- Monitoring indicators for temperature (with warning buzzer), oil pressure and battery charge.
- Throttle lever, fuel gauge and hour meters.

ISEKI SZ SPECIFICATIONS

SZ ZERO-TURN MOWER

ENGINE

Model Iseki EC3D-G01 Diesel

Number of cylinders 3
Displacement 1498cc

Output 33hp@2600 rpm

POWER TRAIN

Transmission type Hydrostatic

Ranges

Speeds Forward: 0 – 17 km/h

Reverse: 0 - 8 km/h

Drive 2WD

MID PTO

Speed 2100 rpm Clutch Multi wet disc

STEERING

Type Two hand levers

BRAKES

Type Dry internal shoe

TYRE SIZE

Front $15 \times 6.0 - 6$ Rear $26 \times 12.0 - 12$

DIMENSIONS

Overall length 2320 mm
Overall width 1480 mm
Overall height folded 1290 mm
Overall height top 1950 mm
Wheel base 1450 mm
Ground clearance 120 mm
Weight 620 kg
Turning circle 0.0 mt

MOWER DECK

Model SSM72
Type Rotary mower
Cutting width 1830 mm

No. of blades 3
Drive Shaft

Rotor drive Double belt Deck lifting Hydraulic

Cutting height 25 – 115 mm by dial Scallop rollers Standard

Scallop rollers Standar Discharge Side

Deck service 45° crank up deck

MOWER DECK DIMENSIONS

Overall width 2280 mm
Overall height 521 mm
Overall length 1165 mm
Weight 210 kg



